

DECLARATION OF PERFORMANCE

1071-CPD-2330

1. Unique identification code of the product-type:
Hunton Silencio (4-36 mm)
Hunton Silencio Thermo (24 and 36 mm)
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:
SB (Soft board)
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
Counterfloor and soundreducing layer for soundproofing floors, with or without water-borne heating system
4. Name and contact address of the manufacturer as required under Article 11(5):
Hunton Fiber AS
Po Box 633
NO-2810 Gjøevik
Norway
5. Where applicable, name and contact address of the authorized representative, specified in Article 12 (2):
Contact the manufacturer
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:
System 3
7. In case of declaration of performance concerning a product covered by a harmonized standard
NS-EN ISO 717-2 SINTEF Byggforsk
EU-notified body No 1071
8. Not applicable
- 9.

Essential characteristics	Performance	Harmonized technical specification
Sound damping 13-15 mm parquet and Silencio 36 mm	Solid concrete: 22-24 dB Hollow concrete: 26-30 dB	NS-EN ISO 717-2
Sound damping 13-15 mm parquet and Silencio Thermo 36mm	Solid concrete: 23-25 dB Hollow concrete: 24-32 dB	
Improvement of airborne soundproofing	3-5 dB	
Reaction to fire	Class E	EN 13986:2004
Design load	Category A	NS 3491-1
Dynamic stiffness, 36 mm	8 MN/m ³	EN ISO 29052-1:1992
Thermal conductivity	0,05	EN 13986:2004
Thermal resistance	0,7 m ² K/W	

10. The performance of the product identified in 1 and 2 is in conformity with the performance in 9

Lars Harald Nilsen, QA & HES Mngr

GJØVIK 28.06.13

Place/Date


HUNTON FIBER AS

Sign